

DB-1 Dual Blower Rack Instructions

Thank you for purchasing a TrimmerTrap product. The DB-1 is designed to use the trailers top rail as a support for the blower in the bottom position on the rack. The DB-1's post must be attached at a height which will allow the blower in the bottom position to sit on the trailers top rail when installed on the rack. Install the rack at a height that will allow the blower to bottom out in the rack's hook at the same time it contacts the trailer's rail. This contact at both points provides support to the top and bottom of the blower. **BLOWERS MUST BE SUPPORTED AT THE TOP AND BOTTOM AND NOT SIMPLY HUNG ON THE HOOK.** A "blower rest" is included for the blower in the top position to sit on.

Attach the rack to a truck or trailer using a minimum of two 3/8" Grade 5 bolts and lock nuts. **Due to Varying Trailer Designs, Attaching Hardware Not Included.** The two attachment bolts must be spaced a **minimum** of 5 vertical inches apart. Drill through the vertical post making certain that the holes are centered in the post. Generally for open trailer applications, the bottom of the post is attached to the trailers main frame and then again to the top rail of the trailer. The trailers bottom and top rail spacing might require the rack to be attached to one of the trailers vertical supports. If the rack is attached to a vertical post, be certain that the vertical post is sufficiently strong enough to support the rack and blowers. Another option is to attach an extension to the bottom of the rack in order to lengthen the rack so that it can be attached to the trailers top and bottom rails.

After the rack is attached, hang the blower to be carried in the top position. Next, install the "blower rest" using one of the "U"-bolts and two lock nuts provided. Slide the rest up until it solidly contacts the bottom of the blower. As with the bottom blower, the top blower should be supported at the top and bottom. Tighten all lock nuts.

Attach both backrest brackets using the "U"-bolts and lock nuts provided. Note: Depending on your blower, it might be necessary to cut off a short section of the threaded studs of the "U" bolt. Adjust the brackets to a height that will allow the use of a stretch cord to be wrapped around the blower. Tighten all lock nuts.

Install the latch into the threaded barrel and securely tighten. A locking compound has been pre-applied to the threads to prevent loosening after being tightened. Now install the plastic plug into the top end of post.

The DB-1 is not compatible with STIHL blowers. For STIHL 300 and 400 series blowers use a TrimmerTrap ST-1. For STIHL 500 and 600 series blowers use a TrimmerTrap ST-2. Some Echo, Kawasaki and Husqvarna model blowers require a TrimmerTrap AK-4 adapter kit. Depending on the frame type, some Echo models might not require the AK-4. To see a complete list of blowers that requires the AK-4 check out or website www.trimmertrap.com or call TrimmerTrap at 1-800-279-8727.

NOTE: IT IS THE PURCHASERS SOLE RESPONSIBILITY TO ASSURE THAT THE RACK IS INSTALLED SAFELY AND SECURELY TO A COMPONENT THAT WILL ADEQUATELY SUPPORT THE EQUIPMENT.

<u>DB-1 Parts List</u>	<u>Quantity</u>
Vertical Post with hooks	one
Flat Backrest Bracket	two
Upper Blower Rest Bracket	one
Latch Assembly	one
Plastic End Plug	one
"U" Bolt	three
1/4 Lock Nut	six

WARRANTY: 90 days against defects in material and workmanship, TrimmerTrap, Inc. reserves the right to repair or replace at its sole discretion the alleged defective TrimmerTrap product. Determination of validity of alleged defect claim will be made upon goods returned to us freight prepaid to our location in Louisville, KY. Call 1-800-279-8727 for a return goods authorization.